



# HALO-B6212

Multi-Tire Bladder Releasing Agent  
PDS

## Description

We combine the high polymerization dimethyl silicone and high reactivity hydroxyl silicone and keep all the good benefits like film-forming, fast-drying, good anti-sagging, and covering ability. After the film form, it will trans to the bladder during the process to protect it and extend its life, also make the multi-releasing works very well.

## Characteristics

- Excellent film-forming and fast drying
- Good anti-sagging
- Multi-releasing type and excellent releasing ability
- Recommend applied with WINSTAR-C, can improve the film-forming ability

## Properties

Appearance	Milky white liquid
Active ingredient(%)	60.0%
pH(5%Solution,25°C)	6.5±1.0
Ionic type	Nonionic
Diluent	Water

## Safety

This document does not contain the safety information required for the product. Please read the safety data sheet for this product before use.

## Storage & packaging

When stored in its originally sealed packaging at 5°C - 40°C, this product may be stored for up to 8 months from its manufacturing date. Comply with the storage instructions marked on the packaging. Once past this expiration date, TAI COUNTY CHEMICAL no longer guarantees that the product meets the sales specifications.

Product comes in 20KG HDPE grey drums and 100kg HDPE blue drums(All breathable).

If it freezes, the best action is to thaw it gradually at room temperature. Do not heat it directly.

## Applications

- Recommend applied with WINSTAR-C for tire multi-releasing
- Directly applied, no need to dilute.
- Could be spraying or smearing by hand or machine.
- Applied in first tire internal and bladder. After drying can start the vulcanization. And applied in tire internal after every 4~5 tires.

## Processing

- HALO-B6212 dilute to 10% and add WINSTAR-C(Filter before packaging and using)

HALO-B6212	:16.7 KG
Water	:83.3 KG
WINSTAR-C	:0.2 KG
Powder	:10 KG
CB-3(Thicker)	:1.5 KG

Total :111.7KG

(Depending on the actual conditions, you can adjust the usage amount.)

**\*Attention: This product will producing some gas, please storage in cool place.**

The data provided above is to the best of our knowledge and experience and is without any warranty. Users should thoroughly test any application and independently conclude satisfactory performance before use.

## TAI COUNTY CHEMICAL

TAIPEI Factory: NO. 91, Museum Rd., Bali Township, Taipei County 24947, Taiwan  
FACTORY REGISTRATION NO: 99.695614.00  
YUNLIN Factory: NO. 1, Changqing St., Lunbei Township, Yunlin County 63745, Taiwan  
FACTORY REGISTRATION NO: 09000892  
Tel: 886-2-2610-4457  
Fax: 886-2-2610-1363  
E-MAIL : [service@taicounty.com.tw](mailto:service@taicounty.com.tw)  
[www.taicounty.com.tw](http://www.taicounty.com.tw)