

WATER POWER WP-711B(30%)

WP-711B(30%)
Smoothness and Softness Terpolymer
Hydrophilic Softener

PDS

Description

WP-711B(30%) is a non-chromatic aberration (non-yellowing) amino silicone fluid which is synthesized by special molecules (be the silicone backbone), to react with the unique hydrophilic functional group. Thanks to this composition, WP-711B(30%) can provide good softness and is far different than any traditional terpolymer hydrophilic softener. WP-711B(30%) cause very low chromatic aberration but with good hand-feeling and hydrophilic ability.

Characteristics

- Good softness
- Low chromatic aberration
- More effective in cotton and cotton blends. Improve excellent softness, but not oily, on the cotton fabrics
- Good hydrophilic ability

Properties

| Appearance | Transparent yellow liquid |
|---------------------|---------------------------|
| Active ingredient(% | %) 30.0% |
| pH(5%Solution,2 | 5°C) 4.5±1.0 |
| Ionic type | Slightly Cationic |
| Diluent | Water |

Safety

This document does not contain the safety information required for the product. Please read the safety data sheet for this product before use.

Storage & packaging

When stored in its originally sealed packaging at 5°C - 40°C, this product may be stored for up to 8 months from its manufacturing date. Comply with the storage instructions marked on the packaging. Once past this expiration date, TAI COUNTY CHEMICAL no longer guarantees that the product meets the sales specifications. Product comes in 120 kg HDPE blue drums.

Applications

- Textile softener
- Suitable for many kinds of fabrics like C, CVC, T/C
- Can combine with NP-911B(30%) to improve the hand-feeling, but doesn't affect the hydrophilic ability

Processing

Padding process

WP-711B(30%) $:5\sim10 \text{ g/L}$

Soaking temperature :Room temperature Setting temperature :150°C/2.5mins (Depending on the actual conditions, you can

adjust the usage amount.)

The data provided above is to the best of our knowledge and experience and is without any warranty. Users should thoroughly test any application and independently conclude satisfactory performance before use.

TAIPEI Factory: NO. 91, Museum Rd., Bali Township, Taipei County 24947, Taiwan
FACTORY REGISTRATION NO: 99.695614.00
YUNLIN Factory: NO. 1, Changqing St., Lunbei Township, Yunlin County 63745, Taiwan
FACTORY REGISTRATION NO: 09000892
Tel: 886-2-2610-4457
Fax: 886-2-2610-1363

E-MAIL: service@taicounty.com.tw www.taicounty.com.tw